




.788 [20.02]
(4 HP, ONE SLOT)



2 FASTENERS FOR ATTACHING MODULE TO THE CHASSIS ARE SPRING-LOADED CAPTIVE SCREWS. WHEN LOOSENED, FASTENERS WILL POP OUT, CREATING TWO GRAB POINTS FOR MODULE EXTRACTION FROM THE CHASSIS.

1. MODULE IS DESIGNED TO BE SUFFICIENTLY COOLED BY A PXI_e CHASSIS THAT MEETS PICMG (COMPACT PCI EXPRESS) STANDARDS. CARE MUST BE TAKEN TO PROVIDE ADEQUATE AIRFLOW AROUND THE CHASSIS AND TO REGULARLY INSPECT AND CLEAN CHASSIS FAN FILTERS TO MAINTAIN OPTIMAL AIRFLOW OVER THE MODULE.

NOTES: (UNLESS OTHERWISE SPECIFIED)



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS SHOWN IN INCHES [MILLIMETERS]
TOLERANCES ARE: .XX [0.X]±.01 [0.25] .XXX [0.XX]±.005 [0.13] ANGLES: ±2° MATERIAL
FINISH

REVISION NOTES	DATE
1. INITIAL RELEASE.	08-24-15

SignalCore Inc. AUSTIN, TEXAS	
TITLE SC5505A, 6 GHz DUAL CHANNEL SOURCE, PXI _e CUSTOMER DRAWING	
SIZE CAGE CODE NO.	DATE OF DRAWING
C 6CG47	08-24-15
SCALE: 1/1	DO NOT SCALE DRAWING
SHEET 1	OF 1