


DIRECT THERMAL ATTACHMENT TO THE TOP SURFACE OF THE RF  
MODULE IS THE PREFERRED MOUNTING METHOD.

NOTES: (UNLESS OTHERWISE SPECIFIED)



<div>UNLESS OTHERWISE SPECIFIED</div> <div>ALL DIMENSIONS SHOWN IN</div> <div>INCHES [MILLIMETERS]</div>		<div>REVISION NOTES</div>		<div>DATE</div>	
<div>TOLERANCES ARE:</div> <div>.XX [0.X]±.01 [0.25]</div> <div>.XXX [0.XX]±.005 [0.13]</div> <div>ANGLES:±2°</div> <div>MATERIAL</div>		1. INITIAL RELEASE.		09-01-13	
		2. DRAWING FORMAT CHANGE.		08-12-15	
<div>FINISH</div>		<div>SignalCore Inc.</div> <div>AUSTIN, TEXAS</div>			
		<div>TITLE</div> <div>SC5506A, 6 GHz DUAL CHANNEL SOURCE</div> <div>CUSTOMER DRAWING</div>			
SIZE		CAGE CODE NO.		DATE OF DRAWING	
C		6CG47		08-12-15	
SCALE:		1/1		DO NOT SCALE DRAWING	
		SHEET		OF	